


430050 ADJUSTABLE FEET Ø95 SANITIZABLE



Internal part made of reinforced polyamide; external covering made of stainless steel AISI 304.
Anti-slip pad made of thermoplastic rubber 68 Shore black. Co-moulded anti-slip pad allows a perfect adherence with steel base. Consequent absence of internal cavities makes foot extremely cleanable. The threaded insert guarantees the protection of the spindle thread.
Locknut available.
*Max. static load (vertical stud).



Code	D	d	A	H	Wrench	h	Kg*
43005009503	95	M16x2	60	103	13	26	2200
43005009504	95	M16x2	90	133	13	26	2200
43005009505	95	M16x2	105	148	13	26	2200
43005009506	95	M16x2	125	168	13	26	2200
43005009507	95	M16x2	155	198	13	26	2200
43005009508	95	M16x2	165	208	13	26	2200
43005009509	95	M16x2	205	248	13	26	2200
43005009510	95	M20x2,5	86	132	17	26	2400
43005009511	95	M20x2,5	116	162	17	26	2400
43005009512	95	M20x2,5	141	187	17	26	2400
43005009513	95	M20x2,5	198	244	17	26	2400
43005009514	95	M24x3	96	142	19	26	2600
43005009515	95	M24x3	122	168	19	26	2600
43005009516	95	M24x3	152	198	19	26	2600
43005009517	95	M24x3	182	228	19	26	2600
43005009518	95	M24x3	300	346	19	26	2600
43005009519	95	M30x3,5	144	190	24	26	2800