

470066 PR DETENT HINGE WITH PRESET POSITIONS AND HOLE COVER CAP



Reinforced polyamide.
Resistant to oils and greases.
Galvanised steel pin.
(1) Pin cap in PA6.
(2) Hole cover cap in reinforced PA6.
The springs that act on the pivot pin have three torque calibrations: 0.7 Nm, 1.1 Nm and 1.7 Nm.
The preset detent positions are: 80° - 115° - 150°.
* Version of the hinge without springs with free movement to 180°.
Working temperature from +65° to -10°.

Code	I	A°	Nm	A	B	H	h	h1	d1	d2
47006605301	34	-	-	51	57	18	10	9	5,5	10,5
47006605302	34	80°	0,7	51	57	18	10	9	5,5	10,5
47006605303	34	80°	1,1	51	57	18	10	9	5,5	10,5
47006605304	34	80°	1,7	51	57	18	10	9	5,5	10,5
47006605305	34	115°	0,7	51	57	18	10	9	5,5	10,5
47006605306	34	115°	1,1	51	57	18	10	9	5,5	10,5
47006605307	34	115°	1,7	51	57	18	10	9	5,5	10,5
47006605308	34	150°	0,7	51	57	18	10	9	5,5	10,5
47006605309	34	150°	1,1	51	57	18	10	9	5,5	10,5
47006605310	34	150°	1,7	51	57	18	10	9	5,5	10,5

