

470072

SOLID CONTROL HANDWHEEL WITH INDICATOR SEAT, REVOLVING HANDLE AND LOCKING KNOB



Code	D	H	d	d2	M	C	C1	d3	d4	d5	d6
47007213000	129	64,5	42	100	27,5	23	14	29	85,7	87,4*	90
47007215000	149	69	42	101	31	25,5	12,5	29	85,7	87,4*	106
47007217000	175	72	40	115	28,5	32	11,5	25	85,7	87,4*	126,5
47007220000	199	71	46	137	24	32	15	29	85,7	87,4*	144

Code	d7	h	h3	h4	h5	h6	R	d8	d1	L	Dm	d1 H10	Q
47007213000	M6	34	10	13,5	12,5	5	54	M8	21	65	20	6,8	24
47007215000	M6	37	9	13,5	12,5	6,5	57	M8	23	76	20	6,8	28
47007217000	M6	38	10	12,5	14	8	60	M8	25	86	20	6,8	28
47007220000	M6	34	11	13,5	12,5	10	74	M8	25	86	22	6,8	23

PA Black reinforced polyamide resistant to oils and greases.

Galvanised steel insert with smooth through bore (tolerance H10).

Brass insert with threaded through hole for the handle. Revolving handle included.



Locking knob included. ATTENTION: dimension Q2 of the locking handwheel must be chosen by the customer based on the dimensions of the machinery on which the handwheel is applied.

Use **gravity indicators 470085**. The indicator and its fixing grub screw (d7) are to be purchased separately. Upon request can be supplied the indicator mounted to the handwheel.

See combinations diameters/indicators:

d5= 87,4 - indicator 4700858...

(*) With adapter 470079 it is possible to use indicator 4700855...



Posición tornillo sin cabeza

