

480074

FILLER BREATHERS WITH DIPSTICKS TMDA-TMDFA-TMDFA/BR



Code without filter	Code with filter	Code with filter BR	F	D	d	d1	h1	h2
48007409101	48007409201	48007409901	G 3/8"	36	23	4	17	11
48007412101	48007412201	48007412901	G 1/2"	41	28	4	18	12
48007419101	48007419201	48007419901	G 3/4"	47	33	5	17	12
48007425101	48007425201	48007425901	G 1"	52	38	5	20	12
48007431101	48007431201	48007431901	G 1 1/4"	63	49	5	23	13
48007438101	48007438201	48007438901	G 1 1/2"	63	55	5	23	13,5
48007414101	48007414201	48007414901	M 14x1,5	41	28	4	21,5	12
48007416101	48007416201	48007416901	M 16x1,5	36	23	4	17	11
48007418101	48007418201	48007418901	M 18x1,5	41	28	4	17,5	12
48007420101	48007420201	48007420901	M 20x1,5	41	28	4	17,5	12
48007422101	48007422201	48007422901	M 22x1,5	41	28	4	17,5	12

Circular head cap with male thread and vertical projections for a better grip. It is manufactured in black with a red cap that includes the graphic fill symbol and the word "OIL". It is equipped with a blued steel level rod.

The standard rod has a length of 200mm.

For orders of more than 250u it can be supplied with a custom length and with "MIN-MAX" markings.

Max. working temperature +90°C.

It has characteristics similar to breather cap 480053-480070. Optionally and for adequate quantities it can be supplied with a flat flexible rod with the inscription "FLEX".

Version with polyurethane foam filter with PPI 60, version with sintered bronze filter with filtration degree of 30μ. Available in 3/8" - 1/2" - 3/4" - 1" NPT thread.

